## 7.5 Ton Front End Loader

# T-REX975S

A passion for performance.
At Revaro, we're not just coming along for the ride. Developing products and services that raise productivity – we are confident we can lower costs and increase profits for industry experts. We are passionate about innovative solutions to help you work smarter – not harder.




1.Weichai high efficiency engine, Tier T3.
2.The energy-saving low-speed engine fits well with the high-efficiency and realizes a comprehensive energy saving of more than 10%.
3.It is applied with the VOLVO HTE220B fixed-shaft electro-hydraulic shift transmission of four forward gears and four reverse gears, which features high transmission efficiency.
4.Fully new generation of boxed frame design by VOLOVO and SDLG team.
5.The load distribution is reasonable; Fatigue test for 200 k Hours, to get the greater reliability.
6.Lift arm uses the lightweight technology, the effective load of each work cycle increased 2%, to achieve the energy saving.
7.Lower resistance bucket: leading board of trapezoidal structure, makes working resistance small, can shovel with hard material, increases 10% in load capacity, improves the working efficiency greatly, reduces the use cost and saves energy.
8.The super-large, full-view, Low noise, Double curved arc front windshield, Luxury seat and User-friendly design, to build the best operating environment. Inner space increased by 15%; Width of view increased by 20%; Sealing property increased by 35%; with powerful air condition.
9.Full-Hydraulic brake system, more sensitive, steady and reliable.

### Specs

| General Specs | |
|---|---|
| Bucket capacity | 4.2m³ |
| Rated load | 7500kg |

| | |
|---|---|
| Operating weight | 24800kg |
| Engine | WP10G270E341 |
| Rated power | 199kW |
| Max Breakout force | 216kN |
| Max Tractive force | 226kN |
| Overall length | 9250mm |
| Fuel tank | 380L |
| Overall width | 3490mm |
| Tire size | 26.5-25 |
| Overall height | 3620mm |
| Wheelbase | 3550mm |
| Ground clearance | 506mm |
| Dumping angle | 45° |
| Dumping height | 3200mm |
| Turning radius at over bucket | 7480mm |
| Turning radius at inside of tires | 6375mm |

Tel: +27 83 408 0607 • Email: ebert.jvrenburg@revaro.co.za • WhatsApp/Cell:
Visit us at4 Alma Road White River, 1240

A member of the REVARO® Group of Companies