## Agrimech Telehandler

# AMT35-70

The AMT35-70 features a powershift Transmission system with torque converter and dual-speed gearbox, controlled via a steering column switch for directional selection and 2 forward/reverse gears. Drive axles employ epicyclic hub reduction with torque differential, ensuring constant 4-wheel drive. Brakes are air-pressure activated drum brakes, with a hand-operated Air disc brake for parking. The boom, made of high-tensile steel, supports low-maintenance UHMWPE pads and a self-leveling carriage with hydraulic quick-hitch. Safety check valves are standard on tilt, telescopic, and lift cylinders.




### Specs

| Specifications | |
|---|---|
| Dimensions | 5870 x 2200 x 2550mm |
| Warranty | 2 year / 2000Hr |
| Engine | YUNNEI YN38GBZ |
| Power | 76kW |
| Bucket Capacity | 1.2-4.0m³ |
| Rated Load | 3,500kg |
| Maximum Lift Height | 7000mm |
| Minimum Turning Radius | 5600mm |
| Maximum Tractive Force | 100kN |
| Maximum Gradeability | 25° |
| Maximum Steering Angle | 30° |
| Oscillation Angle | 8° |
| Engine Type | Water Cooled, four stroke |

Tel: +27 83 408 0607 • Email: ebert.jvrenburg@revaro.co.za • WhatsApp/Cell:
Visit us at4 Alma Road White River, 1240

A member of the REVARO® Group of Companies

| | |
|---|---|
| Displacement | 4.4L |
| Torque Converter | NP280 |
| Gearbox Mode | Electronically controlled |
| Gear Shift | 2 forward - 2 reverse shift |
| Maximum Speed | 30km/h |
| Wheel Base | 3150mm |
| Wheel Tread | 1860mm |
| Ground Clearance | 350mm |
| System Working Pressure | 18-25MPa |
| Boom Lifting Time | 5.6s |
| Total Time | 9.9s |
| Parking Brake | Manual disc brake |
| Tyre Specification | 16/70-20 |