5 Ton Electric Loader

T-REX958E

The High-strength bucket structure provides excellent durability and reliability for demanding applications.



An Intelligent deep-learning control system automatically adjusts power output according to load and vehicle speed.

The intelligent thermal management system regulates cooling for the battery, motor and ECU for reliable operations in varying conditions. LED lighting provides efficient and reliable illumination. High-quality industrial cables offer excellent wear resistance and long service life.

1. Energy saving and high efficiency, fast return on investment.

2. Extremely fast charging, long endurance.

3. Electromotor and automatic transmission, better walking synchronization.

Specs

General Specifications	
Battery Capacity	350kW
Battery Endurance	6-8hours
Battery Voltage	579.6V
Dumping Angle	45
Dumping Height	3060mm
Ground Clearance	435mm
Max. Breakout Force	175kN
Operating Weight	20600kg
Overall Height	3460mm
Overall Length	8770mm

Overall Width	3016mm
Rated Load	5800kg
Rated Power	125kW
Standard Bucket Capacity	3.6m³
Turning Radius at over bucket	7240mm
Turning Radius at inside of tyres	6360mm
Type of Battery	LiFePo4
Wheelbase	3400mm

Tel: +27 83 408 0607 • Email: ebert.jvrenburg@revaro.co.za • WhatsApp/Cell:
Visit us at4 Alma Road White River, 1240

A member of the REVARO® Group of Companies